



SPECS

RAMME	
STØRRELSE	S, M, L, XL
FARGE	Black Diamond / Carbon
RAMME	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
GAFFEL	Fox 34 Float SC Performance Remote, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, remote lockout, custom tuned for Giant
DEMPER	Fox Float DPS Performance Elite, 165/45, custom tuned for Giant
KOMPONENTER	
STYRE	Giant Contact XC Flat, composite, 760x35mm
GRIPS	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
STYRSTEM	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SETEPINNE	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm XL: 150mm travel / 30.9 x 445mm
SADEL	Fi'zik Antares R7 with S-Alloy rails
PEDALER	N/A
DRIVVERK	
GIRHENDLER	Shimano Deore SLX M7100, 1x12
FRONTGIR	N/A
BAKGIR	Shimano Deore SLX RD-M7100
BREMSER	Shimano Deore BR-M6100, hydraulic, Shimano RT-56 rotors [F]180mm, [R]160mm
BREMSEHENDLER	Shimano Deore BL-M6100
KASSETT	Shimano SLX M7100, 10x51
KJEDE	KMC X-12
KRANK	Shimano SLX, 32t S:170mm, M:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano, press fit
HJUL	
FELG	Giant XCR 2 29 Carbon WheelSystem
NAV	Giant XCR 2 29 Carbon WheelSystem
EIKE	Giant XCR 2 29 Carbon WheelSystem
DEKK	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

HØYDEPUNKTER

- Ramme: Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
- Gaffel: Fox 34 Float SC Performance Remote, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, remote lockout, custom tuned for Giant
- Girhendler: Shimano Deore SLX M7100, 1x12
- Krank: Shimano SLX, 32t S:170mm, M:175mm, L:175mm, XL:175mm
- Farge: Black Diamond / Carbon

GEOMETRI

RAMME	S	M	L	XL
Seat Tube Length (mm)	390	420	465	495
Seat Tube Angle	75,5°	75,5°	75,5°	75,5°
Top Tube Length (mm)	572	604	626	653
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	67,5°	67,5°	67,5°	67,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Wheelbase (mm)	1127	1159	1183	1212
Chain Stay Length (mm)	435	435	435	435
Bottom Bracket Drop (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Stand Over Height (mm)	745	750	777	800
Handlebar Width (mm)	760	760	760	760
Stem Length (mm)	60	70	70	70
Crank Length (mm)	170	175	175	175
Wheel Size	29"	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.