FASTROAD SL 1

SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Metal
RAMME	ALUXX SL-Grade Aluminum
GAFFEL	Advanced-Grade Composite, alloy OverDrive steerer
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Connect, flat XS:58cm, S:58cm, M:58cm, M/L:62cm, L:62cm, XL:62cm
GRIPS	Giant Connect Ergo
STYRSTEM	Giant Contact, 8-degree XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SETEPINNE	Giant D-Fuse, alloy, 350mm
SADEL	Giant Approach
PEDALER	platform pedal
DRIVVERK	
GIRHENDLER	Shimano 105, 2x11
FRONTGIR	Shimano 105
BAKGIR	Shimano 105
BREMSER	Tektro HD-R280, Giant MPH rotors [F]160mm, [R]140mm
BREMSEHENDLER	Tektro HD-R280
KASSETT	Shimano CS-HG700, 11x34
KJEDE	KMC X11 with Missing Link
KRANK	FSA Omega, 34/50 XS:170mm, S:170mm, M:170mm, M/L:175mm, L:175mm, XL:175mm
BOTTOM BRACKET	FSA MegaExo, threaded
HJUL	
FELG	Giant double wall aluminum
NAV	Alloy, 28h
EIKE	stainless, 14g
DEKK	Giant S-R3 AC, puncture protect, 700x32c
EXTRAS	35mm max tire size

HØYDEPUNKTER

- Ramme: ALUXX SL-Grade Aluminum
- Gaffel: Advanced-Grade Composite, alloy OverDrive steerer
- Girhendler: Shimano 105, 2x11
- Krank: FSA Omega, 34/50 XS:170mm, S:170mm, M:170mm, M/L:175mm, L:175mm, XL:175mm
- Farge: Metal

GEOMETRI

RAMME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	430	445	460	490	520	550
Seat Tube Angle	73,5°	73,5°	73,0°	73,0°	72,5°	72,5°
Top Tube Length (mm)	540	545	560	575	595	615
Head Tube Length (mm)	105	130	155	180	200	225
Head Tube Angle	71,0°	71,5°	72,0°	72,0°	72,5°	72,5°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	68	64,7	61,5	61,5	58,2	58,2
Wheelbase (mm)	1013	1014	1020	1035	1045	1065
Chain Stay Length (mm)	425	425	425	425	425	425
Bottom Bracket Drop (mm)	70	70	70	70	70	70
Stack (mm)	511	537	563	586	607	631
Reach (mm)	388	386	388	395	403	416
Stand Over Height (mm)	681	697	719	741	767	795
Handlebar Width (mm)	580	580	620	620	620	620
Stem Length (mm)	80	90	100	100	110	110
Crank Length (mm)	170	170	170	175	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.