



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Knight Shield / Reflective Rosewood
RAMME	Advanced-Grade Composite, disc
GAFFEL	Advanced-Grade Composite, hybrid OverDrive 2 steerer, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact SL Aero XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
STYRSTEM	Giant Contact SL Aero XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SETEPINNE	Giant Vector, composite, -5/+15mm offset
SADEL	Giant Fleet SL
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM Rival eTap AXS
FRONTGIR	SRAM Rival eTap AXS
BAKGIR	SRAM Rival eTap AXS
BREMSE	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BREMSEHENDLER	SRAM Rival eTap AXS hydraulic
KASSETT	SRAM Rival, 12-speed, 10x30
KJEDE	SRAM Rival D1
KRANK	SRAM Rival D1 DUB, 35/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit
HJUL	
FELG	Giant SLR 2 Carbon Disc WheelSystem, [F]42mm, [R]65mm
NAV	Giant SLR 2 Carbon Disc WheelSystem, 12mm thru-axle
EIKE	Giant SLR 2 Carbon Disc WheelSystem
DEKK	Giant Gavia AC 1, tubeless,700x25c (26.5mm), folding
EXTRAS	tubeless prepared, 28mm max tire size

HØYDEPUNKTER

- Ramme: Advanced-Grade Composite, disc
- Gaffel: Advanced-Grade Composite, hybrid OverDrive 2 steerer, disc
- Girhendler: SRAM Rival eTap AXS
- Krank: SRAM Rival D1 DUB, 35/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farge: Knight Shield / Reflective Rosewood

GEOMETRI

RAMME	XS	S	M	ML	L	XL
Seat Tube Length (mm)	465	500	520	545	575	595
Seat Tube Angle	74,5°	73,5°	73,0°	73,0°	73,0°	72,0°
Top Tube Length (mm)	515	535	550	570	580	605
Head Tube Length (mm)	120	130	145	165	185	200
Head Tube Angle	71,0°	72,5°	73,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	45	45	45	45	45	45
Trail (mm)	70	60	57	57	57	57
Wheelbase (mm)	972	970	976	997	1007	1021
Chain Stay Length (mm)	405	405	405	405	405	405
Bottom Bracket Drop (mm)	70	68	68	65	65	65
Stack (mm)	517	529	545	562	581	595
Reach (mm)	372	378	383	398	402	412
Stand Over Height (mm)	744	769	787	807	829	843
Handlebar Width (mm)	400	400	420	420	440	440
Stem Length (mm)	80	90	100	110	110	120
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700C	700C	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.