



SPECS

| RAMME | |
|----------------|--|
| STØRRELSE | XS, S, M, M/L, L, XL |
| FARGE | Starry Night / Chameleon Neptune, Panther / Chameleon Saturn |
| RAMME | Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout |
| GAFFEL | Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc |
| DEMPER | N/A |
| KOMPONENTER | |
| STYRE | Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm |
| GRIPS | Stratus Lite 3.0 |
| STYRSTEM | Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm |
| SETEPINNE | Giant D-Fuse, composite, 14mm offset |
| SADEL | Giant Approach |
| PEDALER | N/A |
| DRIVVERK | |
| GIRHENDLER | Shimano GRX RX-600, 2x11 |
| FRONTGIR | Shimano GRX RX-810 |
| BAKGIR | Shimano GRX RX-810 |
| BREMSE | Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm |
| BREMSEHENDLER | Shimano GRX RX-600 hydraulic |
| KASSETT | Shimano 105, 11-speed, 11x34 |
| KJEDE | KMC X11SL-1 |
| KRANK | FSA Omega AGX, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | Praxis, press fit |
| HJUL | |
| FELG | Giant P-X2 Disc wheelset |
| NAV | Giant P-X2 Disc wheelset |
| EIKE | Giant P-X2 Disc wheelset |
| DEKK | Giant CrossCut AT 1, 700x38c, tubeless |
| EXTRAS | tubeless prepared, 53mm max tire size in "long" flip chip position, 42mm max tire size in "short" flip chip position |

HØYDEPUNKTER

- Ramme: Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
- Gaffel: Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
- Girhendler: Shimano GRX RX-600, 2x11
- Krank: FSA Omega AGX, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farge: Starry Night / Chameleon Neptune, Panther / Chameleon Saturn

GEOMETRI

| RAMME | XS | | S | | M | | ML | | L | | XL |
|--------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------|-------|-------|-------|-------|
| | SHORT | LONG | SHORT | LONG | SHORT | LONG | SHORT | LONG | SHORT | LONG | SH |
| Seat Tube Length (mm) | 430 | 450 | 470 | 490 | 510 | 530 | | | | | |
| Seat Tube Angle | 74,0° | 73,5° | 73,5° | 73,0° | 73,0° | 73,0° | 73,0° | 73,0° | 73,0° | 73,0° | 73,0° |
| Top Tube Length (mm) | 540 | 550 | 560 | 575 | 585 | 600 | | | | | |
| Head Tube Length (mm) | 125 | 135 | 150 | 165 | 180 | 195 | | | | | |
| Head Tube Angle | 70,0° | 71,0° | 71,5° | 72,0° | 72,0° | 72,0° | | | | | |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 | 50 | | | | | |
| Trail (mm) | 78 82 | 72 75 | 68 72 | 65 68 | 65 68 | 65 68 | | | | | |
| Wheelbase (mm) | 1024 1034 | 1020 1030 | 1026 1036 | 1031 1041 | 1041 1051 | 1051 1061 | | | | | |
| Chain Stay Length (mm) | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | | | | | |
| Bottom Bracket Drop (mm) | 80 81 | 80 81 | 80 81 | 80 81 | 80 81 | 80 81 | | | | | |
| Stack (mm) | 556 | 570 | 586 | 602 | 616 | 630 | | | | | |
| Reach (mm) | 381 | 381 | 387 | 391 | 397 | 407 | | | | | |
| Stand Over Height (mm) | 724 731 | 740 747 | 757 764 | 774 780 | 791 797 | 807 814 | | | | | |
| Handlebar Width (mm) | 420 | 420 | 440 | 440 | 460 | 460 | | | | | |
| Stem Length (mm) | 50 | 60 | 70 | 80 | 80 | 90 | | | | | |
| Crank Length (mm) | 170 | 170 | 172,5 | 172,5 | 175 | 175 | | | | | |
| Wheel Size | 700C | 700C | 700C | 700C | 700C | 700C | | | | | |

Alle spesifikasjonene kan endres uten varsel.