



SPECS

RAMME	
STØRRELSE	XS, S, M, M/L, L, XL
FARGE	Grenadine, Deep Lake
RAMME	ALUXX-Grade Aluminum, 12x142mm thru-axle, disc, flip chip dropout
GAFFEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	cork tape with gel
STYRSTEM	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SETEPINNE	Giant D-Fuse, alloy, 14mm offset
SADEL	Giant Approach
PEDALER	N/A
DRIVVERK	
GIRHENDLER	Shimano GRX RX-400, 2x10
FRONTGIR	Shimano Tiagra
BAKGIR	Shimano GRX RX-400
BREMSER	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSEHENDLER	Shimano GRX RX-400 hydraulic
KASSETT	Shimano HG500, 11x34
KJEDE	KMC X10 with Missing Link
KRANK	FSA Omega Adventure, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
BOTTOM BRACKET	FSA Mega EXA, press fit
HJUL	
FELG	Giant S-X2 Disc wheelset
NAV	Giant S-X2 Disc wheelset
EIKE	Giant S-X2 Disc wheelset
DEKK	Giant CrossCut AT 2, 700x38c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 42mm max tire size in "short" flip chip position

HØYDEPUNKTER

- Ramme: ALUXX-Grade Aluminum, 12x142mm thru-axle, disc, flip chip dropout
- Gaffel: Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
- Girhendler: Shimano GRX RX-400, 2x10
- Krank: FSA Omega Adventure, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farge: Grenadine, Deep Lake

GEOMETRI

RAMME	XS	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Seat Tube Length (mm)	430	450	470	490	510	530
Seat Tube Angle	74,0°	73,5°	73,5°	73,0°	73,0°	73,0°
Top Tube Length (mm)	540	550	560	575	585	600
Head Tube Length (mm)	125	135	150	165	180	190
Head Tube Angle	70,0°	71,0°	71,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68
Wheelbase (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1050 1060
Chain Stay Length (mm)	430 440	430 440	430 440	430 440	430 440	430 440
Bottom Bracket Drop (mm)	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	404
Stand Over Height (mm)	717 724	734 741	752 759	769 776	786 793	803 810
Handlebar Width (mm)	420	420	440	440	460	460
Stem Length (mm)	70	80	90	100	100	110
Crank Length (mm)	170	170	172,5	172,5	175	175
Wheel Size	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C

Alle spesifikasjonene kan endres uten varsel.