



SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl GO integrated in TT, RideControl Ergo 3
DISPLAY	ANT+ cycle computer compatible
BATTERI	EnergyPak Smart 400,EnergyPak Plus range extender compatible
RAMME	
STØRRELSE	S, M, L, XL
FARGE	Amber Glow/Cordovan
RAMME	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
GAFFEL	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Boost 110x15QR
DEMPER	Fox DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned
KOMPONENTER	
STYRE	Giant Contact SL 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, single lock-on
STYRSTEM	Giant Contact SL 35
SETEPINNE	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SADEL	Giant Romero, Neutral
PEDALER	n/a
DRIVVERK	
GIRHENDLER	Shimano Deore SLX
FRONTGIR	MRP HD2 co-moulded chain guide
BAKGIR	Shimano Deore SLX, 12-speed, Shadow+
BREMSER	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
BREMSEHENDLER	Shimano SLX, I-spec EV
KASSETT	Shimano HG-M6100, 10-51T, 12-speed
KJEDE	KMC e.12 Sport, NP/NP, e-bike optimized
KRANK	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160, M/L: 165, XL:170)
BOTTOM BRACKET	n/a

HJUL	
FELG	Giant AM 29" [F]/ 27.5" [R], Tubeless ready, 30mm inner width, e-bike optimized
NAV	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
EIKE	Sapim E-Lite [R] Race [F], e-bike optimized
DEKK	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
TILBEHØR	
LYS	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRI

RAMME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	77,2° 78,0°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Top Tube Length (mm)	577 575	607 605	636 634	665 663
Head Tube Length (mm)	95	100	115	130
Head Tube Angle	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	113,1 108	113,1 108	113,1 108	113,1 108
Wheelbase (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Chain Stay Length (mm)	447 447	447 447	447 447	447 447
Bottom Bracket Drop (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Stand Over Height (mm)	726 735	733 742	732 741	741 750
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	160	165	165	170
Wheel Size	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Alle spesifikasjonene kan endres uten varsel.