

TRANCE X E+ 2



SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl GO integrated in TT, RideControl Ergo 3
DISPLAY	ANT+ Wireless display compatible
BATTERI	EnergyPak Smart 800, EnergyPak Plus 250Wh range extender compatible
RAMME	
STØRRELSE	S, M, L, XL
FARGE	Messier/Black
RAMME	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
GAFFEL	Fox 36 Float Rhythm, 150mm travel, 44mm offset, EVOL, Grip Damper, Sweep adjust, Boost 110x15QR, e-optimized
DEMPER	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned
KOMPONENTER	
STYRE	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant New trail grip Half-waffle/single lock-on
STYRSTEM	Giant Contact SL 35
SETEPINNE	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SADEL	Giant Romero E
PEDALER	Flat pedal
DRIVVERK	
GIRHENDLER	Shimano SLX
FRONTGIR	MRP HD2 co-moulded chain guide
BAKGIR	Shimano SLX, 12-speed, Shadow+
BREMSER	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
BREMSEHENDLER	Shimano Deore
KASSETT	Shimano CS-M6100-12, 10-51T, 12-speed
KJEDE	KMC e.12 Turbo, EcoProteq, e-bike optimized
KRANK	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	n/a

HJUL	
FELG	Giant AM 29", Tubeless ready, 30mm inner width
NAV	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
EIKE	Sapim E-Lite [R] Race [F], e-bike optimized
DEKK	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
TILBEHØR	
LAS	Torx 25 Battery Lock with built-in Torque limiter

GEOMETRI

RAMME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Top Tube Length (mm)	577 575	610 605	637 635	667 665
Head Tube Length (mm)	95	100	110	120
Head Tube Angle	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	117 122,4	117 122,4	117 122,4	117 122,4
Wheelbase (mm)	1205 1206	1239 1237	1268 1269	1300 1301
Chain Stay Length (mm)	473 473	473 473	473 473	473 473
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	611 605	621 614	630 624
Reach (mm)	439 447	457 462	482 489	510 517
Stand Over Height (mm)	783 789	775 784	763 770	775 782
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	50	50	60
Crank Length (mm)	160	165	165	170
Wheel Size	29"	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.