



SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	SyncDrive Core, 50Nm, Powered by Yamaha
SENSOR	RideControl Dash
DISPLAY	RideControl Dash, full color lcd screen
BATTERI	EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion
RAMME	
STØRRELSE	XS, S, M, L, (XS-S: 27.5, M-L: 29er)
FARGE	Aged Denim
RAMME	ALUXX aluminum, Overdrive 1½ - 1⅙" head tube, integrated KSA18 kickstand mount
GAFFEL	SR Suntour XCM 32 ATB Coil, NLO, 29"/27.5", 100mm travel, Tapered 1½ - 1⅙" steerer (XS-S: 27.5", M-L: 29")
DEMPER	n/a
KOMPONENTER	
STYRE	Giant Connect TR Riser 31.8x750mm (XS-S), 780mm (M-L)
STYRSTEM	Giant Contact
SETEPINNE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADEL	Liv Sport
PEDALER	Aluminum Platform
DRIVVERK	
GIRHENDLER	Shimano Altus
FRONTGIR	n/a
BAKGIR	Shimano Alivio, M3100, 9-speed
BREMSE	Tektro HD-M286, hydraulic disc, 180mm[F], 160mm[R]
BREMSEHENDLER	Tektro HD-M286
KASSETT	Shimano CS-HG200, 11-36T
KJEDE	KMC e.9 Sport, e-bike optimized
KRANK	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T

HJUL	
FELG	Liv, GX03V, 27.5 / 29, Alluminum(XS-S: 27.5, M-L: 29er)
NAV	Giant eTracker Sport, [F] 9mm QR [R] 135mm QR
EIKE	Stainless steel
DEKK	Maxxis Rekon 27.5x2.4" / 29 x 2.4" Wire Bead 60TPI (XS-S: 27.5, M-L: 29er)

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	365	405	445	485
Seat Tube Angle	74,0°	73,5°	73,0°	73,0°
Top Tube Length (mm)	545	570	595	615
Head Tube Length (mm)	105	115	105	115
Head Tube Angle	68,0°	68,0°	68,0°	68,0°
Fork Rake (mm)	42	42	46	46
Trail (mm)	104	104	99	99
Wheelbase (mm)	1112	1132	1159	1179
Chain Stay Length (mm)	475	475	475	475
Bottom Bracket Drop (mm)	50	50	45	45
Stack (mm)	591	600	603	612
Reach (mm)	376	392	411	428
Stand Over Height (mm)	693	722	761	768
Handlebar Width (mm)	690	690	750	750
Stem Length (mm)	40	40	50	60
Crank Length (mm)	165	165	170	170
Wheel Size	27.5"	27.5"	29"	29"

Alle spesifikasjonene kan endres uten varsel.